



A = CLEARANCE MEASURED [IN.]	QMHSB SERVICE LOAD [LBS]*	QMHLB SERVICE LOAD [LBS]*
1/8	34.6	80.6
3/16	80.4	124.8
1/4	126.3	169.0
5/16	172.0	213.2
3/8	217.9	257.4
7/16	263.7	301.6
1/2	309.5	345.8
9/16	355.3	390.0
5/8	401.1	434.3
11/16	447.0	478.5
3/4	492.8	522.7

*SERVICE LOAD IS THE AVGERAGE LOAD WHICH CAUSES THE HOOK TO TOUCH THE TILE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUICK MOUNT PV. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUICK MOUNT PV IS PROHIBITED.

DO NOT SCALE DRAWING

Quick Mount PV[®]

TITLE: QUICK HOOK FOR BOTTOM MOUNTED RAILS, SERVICE DEFLECTION CLEARANCE

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/8 TWO PLACE DECIMAL ±.18 THREE PLACE DECIMAL ±.125	SIZE	DRAWN BY: RAD	REV
	A	DATE: 2/26/2016	1
SCALE: 1:6	WEIGHT: 51.99	SHEET 1 OF 1	